

Appl. No. 10/710,439  
Amdt. dated March 20, 2006  
Reply to Office action of December 28, 2005

**Amendments to the Claims:**

This listing of claims will replace all prior versions and listings of claims in the application:

**Listing of Claims:**

1 (currently amended): An ultra-thin backlight display panel comprising:

5       an upper housing having a first cold cathode fluorescent lamp (CCFL)  
for generating light and a first lampshade for collecting light generated by  
the first CCFL;

      a lower housing having a second CCFL for generating light and a  
second lampshade for collecting light generated by the second CCFL; and

10       a backlight module having a light guide plate, a transparent film, and a  
reflection film, the light guide plate having four sides, wherein two of the  
four sides are connected with the upper housing and the lower housing, and  
the other two sides are respectively covered with a reflective material, the  
transparent film being positioned on a first plane of the light guide plate and  
15       the reflection film being positioned on a second plane of the light guide  
plate to reflect light from the first CCFL and the second CCFL;

      wherein the reflective materials covering the two sides of the light  
guide plate reflect light from the light guide plate back, and

wherein the upper housing has an upper base and an upper cover  
20       installed on the upper base in a rotatable manner and the upper cover is capable  
      of clipping the transparent film on the first plane of the light guide plate.

2 (original): The ultra-thin backlight display panel of claim 1 wherein a  
thickness of the backlight module is about one centimeter.

25

3 (currently amended): The ultra-thin backlight display panel of claim 1  
wherein ~~the upper housing has an upper base and an upper cover installed~~

Appl. No. 10/710,439  
Amdt. dated March 20, 2006  
Reply to Office action of December 28, 2005

~~on the upper base in a rotatable manner,~~ the lower housing has a lower base and  
[[an]] a lower cover installed on the lower base in a rotatable manner, and ~~the~~  
~~upper cover and the lower cover are~~ is capable of clipping the transparent  
film on the first plane of the light guide plate.

5

4 (original): The ultra-thin backlight display panel of claim 1 wherein the  
transparent film is capable of diffusing light.

5 (original): The ultra-thin backlight display panel of claim 1 wherein the  
10 upper housing has at least one opening for connecting a fixture that is used  
for placing the ultra-thin backlight display panel.